

MESSING

Ø STÆNGER



LEGERING CW614N / CUZN39PB3 - CW608N / CUZN38PB2 (BUKBAR)

LÆNGDE Ø 1 - 65 (3000 - 4000 MM), Ø 70 - 400 (1000 - 2250 MM)

KG/MTR	Ø		KG/MTR	Ø	
0,01	1	T	0,81	11	T
0,02	1,5	T	0,88	11,5	T
0,03	2	T	0,96	12	T/B
0,04	2,5	T	1,04	12,5	T
0,06	3	T/B	1,13	13	T
0,08	3,5	T	1,22	13,5	T
0,11	4	T/B	1,31	14	T
0,14	4,5	T	1,40	14,5	T
0,17	5	T/B	1,50	15	T/B
0,20	5,5	T	1,71	16	T
0,24	6	T/B	1,93	17	T
0,26	6,3	T	2,16	18	T
0,28	6,5	T	2,41	19	T
0,33	7	T/B	2,67	20	T/B
0,38	7,5	T	2,94	21	T
0,43	8	T/B	3,23	22	T
0,48	8,5	T	3,53	23	T
0,54	9	T	3,85	24	T
0,60	9,5	T	4,18	25	T/B
0,67	10	T/B	4,51	26	T
0,74	10,5	T	4,87	27	T

Noter: Ø=Diameter, T=Trukket, P=Presset, S=Støbt, B=Bukke kvalitet

MESSING



Ø STÆNGER

LEGERING CW614N / CuZn39Pb3

LÆNGDE Ø 1 - 65 (3000 - 4000 MM), Ø 70 - 400 (1000 - 2250 MM)

KG/MTR	Ø		KG/MTR	Ø	
5,23	28	T	20,94	56	T
5,61	29	T	24,03	60	T
6,01	30	T	28,21	65	T
6,84	32	T	32,71	70	P
7,27	33	T	37,55	75	P
7,72	34	T	42,73	80	P
8,18	35	T	48,23	85	P
8,65	36	T	54,07	90	P
9,14	37	T	60,25	95	P
9,64	38	T	66,67	100	P
10,15	39	T	73,60	105	P
10,68	40	T	80,78	110	P
11,22	41	T	88,29	115	P
11,78	42	T	96,13	120	P
13,52	45	T	104,31	125	P
15,38	48	T	112,82	130	P
16,69	50	T	130,85	140	P
18,05	52	T	150,21	150	P
19,47	54	T	170,91	160	P
20,19	55	T	192,93	170	P

Noter: Ø=Diameter, T=Trukket, P=Presset, S=Støbt, B=Bukkekalitet

MESSING



Ø STÆNGER

LEGERING CW614N / CUZN39PB3

LÆNGDE Ø 1 - 65 (3000 - 4000 MM), Ø 70 - 400 (1000 - 2250 MM)

KG/MTR	Ø		KG/MTR	Ø	
216,30	180	P	417,24	250	P
267,04	200	P	1068,15	400	S
337,80	225	P			

Noter: Ø=Diameter, T=Trukket, P=Presset, S=Støbt, B=Bukke kvalitet

“

BRANCHENS STØRSTE SORTIMENT
— SE OGSÅ VORES STORE LAGERPROGRAM I
EMNERØR PÅ SIDE 94 - 96

”